Product data sheet
Characteristics

A9F84340
Miniature circuit breaker (MCB), Acti9 iC60H, 3P, 40A, C curve, 10000A (IEC/EN 60898-1), 15kA (IEC/EN 60947-2)



Main

Range	Acti9
Product name	Acti9 iC60
Product or component type	Miniature circuit-breaker
Device short name	iC60H
Device application	Distribution
Poles description	3P
Number of protected poles	3
[In] rated current	40 A
Network type	DC AC
Trip unit technology	Thermal-magnetic
Curve code	C
Utilisation category	Category A conforming to EN/IEC 60947-2
Suitability for isolation	Yes conforming to EN/IEC 60947-2 Yes conforming to EN/IEC 60898-1
Standards	EN/IEC 60947-2 EN/IEC 60898-1

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	12...133 V AC 50/60 Hz 220...240 V AC 50/60 Hz 380...415 V AC 50/60 Hz 440 V AC 50/60 Hz <= 180 V DC
Magnetic tripping limit	8 x In +/- 20 %
Breaking capacity	42 KA Icu at 12...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 30 KA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 KA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 KA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 KA Icu at <= 180 V DC conforming to EN/IEC 60947-2 10000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1
[Ics] rated service breaking capacity	21 KA 50 % x Icu at 12...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 KA 50 % x Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 7.5 KA 50 % x Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 5 KA 50 % x Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 KA 100 % x Icu at <= 180 V DC conforming to EN/IEC 60947-2
Limitation class	3 conforming to EN/IEC 60898-1
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 KV conforming to EN/IEC 60947-2
Contact position indicator	Yes

Control type	Toggle
Local signalling	Trip indicator
Mounting mode	Clip-on Removable comb busbar installed
Mounting support	35 mm DIN rail
Comb busbar and distribution block compatibility	Top or bottom: YES
Connection pitch	18 Mm between phases
9 mm pitches	6
Height	85 Mm
Width	54 Mm
Depth	78.5 Mm
Net weight	0.375 Kg
Colour	White
Mechanical durability	20000 Cycles
Electrical durability	10000 Cycles
Connections - terminals	Single terminal (top or bottom) , for 1 cable(s) , 1…35 mm^2, rigid, copper Single terminal (top or bottom) , for 3.0 cable(s) , 16 mm^2, rigid, copper, with accessory Single terminal (top or bottom) , for 1.0 cable(s) , 50 mm^2, rigid, aluminium, with accessory Single terminal (top or bottom) , for 1.0 cable(s) , 1…25 mm^2, flexible, copper Single terminal (top or bottom) , for 1.0 cable(s) , 1…25 mm^2, flexible with ferrule, copper Single terminal (top or bottom) , for 1.0 cable(s) , flexible, copper or aluminium, with ring terminal a Single terminal (top or bottom) , for 3 cable(s) , 10 mm^2, flexible, copper, with accessory
Wire stripping length	14 Mm for top or bottom connection
Tightening torque	3.5 N.M top or bottom
Earth-leakage protection	Separate block

Environment

IP degree of protection	IP20 conforming to IEC 60529 IP40 in modular enclosure (Insulation class II) conforming to IEC 60529
Pollution degree	3 conforming to EN/IEC 60947-2
Overvoltage category	IV
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	0...2000 m
Ambient air temperature for operation	-35…70 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.500 Cm
Package 1 Width	5.400 Cm
Package 1 Length	9.500 Cm
Package 1 Weight	361.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	8.000 Cm
Package 2 Width	9.800 Cm
Package 2 Length	22.500 Cm
Package 2 Weight	1.502 Kg
Unit Type of Package 3	S03
Number of Units in Package 3	44
Package 3 Height	30 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm
Package 3 Weight	17.075 Kg

Offer Sustainability

Recyclability potential, in %	54
Total lifecycle Carbon footprint	62 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2.469001627750856
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.04810693051761632
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.03190006242955235
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	58.16700000000002
Carbon footprint of the use phase [B2, B3, B4, B6]	58 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	1.0085230420790305
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	62
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
OECD PFAS Regulation	Item contains PFAS Chemicals
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes
Silicone-free	No
End of life manual availability	No need of specific recycling operations
WEEE Label	The product must be disposed on European Union markets following specific waste collection a