Product data sheet
Characteristics

EOCRSSD-30W
Electronic overcurrent relay, EOCR Digital, 3 to 30A, 440VAC



Main

Range of product	EOCR
Device short name	EOCR-SSD
Product or component type	Protection relay
Protection type	Overload, In > OC setting Sensitivity to phase loss Locked rotor for starting, In > 2 times OC setting
Product specific application	Overcurrent protection
Network type	AC
Network frequency	50...60 Hz
Thermal protection adjustment range	3…30 A
Tripping threshold	3...30 A

Complementary

[Us] rated supply voltage	440 V AC
Mounting support	35 mm DIN rail Panel
Contacts type and composition	1 NC + 1 NO (OL)
Short-circuit and overload protection	By 4 A gG fuse
[Ue] rated operational voltage	600 V AC 50...60 Hz for power circuit conforming to UL 690 V AC 50...60 Hz for power circuit conforming to CSA 690 V AC 50...60 Hz for power circuit conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60947-4-1
Reset	Manual reset Electrical 0…1 s by interruption of power supply
Time delay type	D-Time: 1...30 s O-Time: 0.5, 1...10 s
Display type	7 segments LED
Power consumption in W	3 W
Connections - terminals	Control circuit: lug-clamp 2 x 1…2.5 mm²flexible without cable end - M3.5 Control circuit: cable 2 x 1…2.5 mm²flexible without cable end - M3.5 Control circuit: cable 2 x 1…2.5 mm²flexible with cable end - M3.5
Tightening torque	Control circuit: 1.7 N.m on lug-clamp, cable, 7 mm
Height	70 Mm
Width	56 Mm
Depth	77.2 Mm
Net weight	0.255 Kg

Environment

Standards	IEC 60947-4-1
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20…60 °C conforming to IEC 60947-4-1
Ambient air temperature for storage	-30…80 °C
Operating altitude	2000 m
Fire resistance	650 °C conforming to IEC 60695-2-12 960 °C conforming to UL 94
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-7
Vibration resistance	4 gn on panel mounting conforming to IEC 60068-2-6 2 gn on 35 mm DIN rail conforming to IEC 60068-2-6
Dielectric strength	2 KV 50...60 Hz in between case and circuit conforming to IEC 60255-5 1 KV 50...60 Hz in between contact conforming to IEC 60255-5 2 KV 50...60 Hz in between circuit conforming to IEC 60255-5
Surge withstand	6 KV conforming to IEC 61000-4-5
Electromagnetic compatibility	Resistance to radiated electromagnetic fields: 10 V/m level 3 conforming to IEC 61000-4-3 Resistance to electrostatic discharge: 8 kV air, 6 kV contact conforming to IEC 61000-4-2 Resistance to fast transient: 2 kV conforming to IEC 61000-4-4 Conducted RF disturbances: 10 V conforming to EN 61000-4-6 Conducted RF disturbances: class A conforming to EN 55011
[Ith] conventional free air thermal current	5 A for control circuit
Permissible current	250 V, 5 A

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.9 Cm
Package 1 Width	8.2 Cm
Package 1 Length	7.9 Cm
Package 1 Weight	196.0 G

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
Take-back	No

Product Life Status : Commercialised