Product data sheet
Characteristics

EZ9F34363
Miniature circuit breaker (MCB), Easy9, 3P, 63A, C curve, 4500A (IEC/EN 60898-1)



Main

Range	Easy9
Device application	Distribution
Product or component type	Miniature circuit-breaker
Device short name	Easy9 MCB
Poles description	3P
Number of protected poles	3
[In] rated current	63 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	4500 A Icn at 230 V AC 50/60 Hz conforming to IEC 60898-1 4500 A Icn at 400 V AC 50/60 Hz conforming to IEC 60898-1
Suitability for isolation	Yes conforming to IEC 60898-1

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	400 V AC 50/60 Hz
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	4.5 KA 100 % x Icn at 400 V AC 50/60 Hz conforming to IEC 60898-1
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60898-1
[Uimp] rated impulse withstand voltage	4 KV conforming to IEC 60898-1
Contact position indicator	Yes
Control type	Toggle
Local signalling	Without
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 Mm
Width	54 Mm
Depth	66.5 Mm
Colour	Grey (RAL 7035)
Mechanical durability	10000 Cycles
Electrical durability	4000 Cycles
Connections - terminals	Tunnel type terminal (top or bottom) 1…25 mm² flexible Tunnel type terminal (top or bottom) 1…35 mm² rigid
Tightening torque	3.5 N.M top or bottom
Earth-leakage protection	Without

Environment

Standards	IEC 60898-1
Product certifications	GOST-R
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	2
Tropicalisation	2
Relative humidity	95 % at -25…60 °C
Ambient air temperature for operation	-25…60 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.500 Cm
Package 1 Width	5.400 Cm
Package 1 Length	8.500 Cm
Package 1 Weight	364.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	8.500 Cm
Package 2 Width	9.000 Cm
Package 2 Length	23.000 Cm
Package 2 Weight	1.527 Kg
Unit Type of Package 3	S03
Number of Units in Package 3	48
Package 3 Height	30.000 Cm
Package 3 Width	30.000 Cm
Package 3 Length	40.000 Cm
Package 3 Weight	19.006 Kg

Offer Sustainability

Recyclability potential, in %	59
Total lifecycle Carbon footprint	69 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2.24204320557491
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.0481220905923344
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0549467595818815
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	65.2975609756097
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	65 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.946478048780487
Carbon footprint of the end-of-life phase [C1 to C4]	0.9 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	69
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	0dbcf8b1-4732-4e36-88bc-462a078c2d4c
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant

California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the S
Halogen-free status	Product contains halogen above thresholds
PVC free	No
Silicone-free	No
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised