SIEMENS

Data sheet 6ES7134-6JD00-0DA1



SIMATIC ET 200SP, Analog input module, AI 4xTC High Speed, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%

General information	
Product type designation	AI 4xTC HS
HW functional status	FS22 or higher
Firmware version	V2.0.0
● FW update possible	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color-coded label	CC00
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
● Measuring range scalable	Yes
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V21.1 or higher
● STEP 7 configurable/integrated from version	configurable as of V5.7.3.3 with HSP0348 V3.0 / integrated as of V5.7.5.0
● PROFIBUS from GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
● PROFINET from GSD version/GSD revision	GSDML V2.50
Operating mode	
● Oversampling	No
● MSI	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	37 mA
Current consumption, max.	50 mA
Power loss	
Power loss, typ.	0.9 W
Address area	
Address space per module	
● Address space per module, max.	16 byte; + 1 byte for QI information
Hardware configuration	

Subject to change without notice
© Copyright Siemens

Automatic encoding	Yes
● Mechanical coding element	Yes
● Type of mechanical coding element	Type A
Selection of BaseUnit for connection variants	
● 2-wire connection	BU type A0, A1
Analog inputs	
Number of analog inputs	4
● For voltage measurement	4
● For thermocouple measurement	4
permissible input voltage for voltage input (destruction limit), max.	30 V
Cycle time (all channels), min.	5 ms; Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels)
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
● -1 V to +1 V	Yes; 16 bit incl. sign
— Input resistance (-1 V to +1 V)	1 MΩ
● -250 mV to +250 mV	Yes; 16 bit incl. sign
— Input resistance (-250 mV to +250 mV)	1 MΩ
● -50 mV to +50 mV	Yes; 16 bit incl. sign
— Input resistance (-50 mV to +50 mV)	1 MΩ
● -80 mV to +80 mV	Yes; 16 bit incl. sign
— Input resistance (-80 mV to +80 mV)	1 MΩ
Input ranges (rated values), thermocouples	
● type B	Yes; 16 bit incl. sign
— Input resistance (Type B)	1 MΩ
● type C	Yes; 16 bit incl. sign
— Input resistance (Type C)	1 MΩ
● Type E	Yes; 16 bit incl. sign
— Input resistance (Type E)	1 MΩ
● Type J	Yes; 16 bit incl. sign
— Input resistance (type J)	1 MΩ
● Type K	Yes; 16 bit incl. sign
— Input resistance (Type K)	1 MΩ
● Type L	Yes; 16 bit incl. sign
— Input resistance (Type L)	1 MΩ
● Type N	Yes; 16 bit incl. sign
— Input resistance (Type N)	1 MΩ
● Type R	Yes; 16 bit incl. sign
— Input resistance (Type R)	1 MΩ
● Type S	Yes; 16 bit incl. sign
— Input resistance (Type S)	1 MΩ
● Type T	Yes; 16 bit incl. sign
— Input resistance (Type T)	1 MΩ
● Type U	Yes; 16 bit incl. sign
— Input resistance (Type U)	1 MΩ
● Type TXK/TXK(L) to GOST	Yes; 16 bit incl. sign
— Input resistance (Type TXK/TXK(L) to GOST)	1 MΩ
Thermocouple (TC)	
Temperature compensation	
— Parameterizable	Yes
— Reference channel of the module	No
— internal comparison point	Yes; with BaseUnit type A1
— Reference channel of the group	Yes
— Number of reference channel groups	4; Group 0 to 3
— fixed reference temperature	Yes
Cable length	
● shielded, max.	200 m; 100 m for thermocouples
Analog value generation for the inputs	

Subject to change without notice
© Copyright Siemens

Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
● Integration time, parameterizable	Yes
● Basic conversion time, including integration time (ms)	
— additional processing time for wire-break check	1 ms
● Interference voltage suppression for interference frequency f1 in Hz	16.6 / 50 / 60 Hz / off
● Conversion time (per channel)	180/60/50/1.25 ms
Smoothing of measured values	
● Number of smoothing levels	4
● parameterizable	Yes
● Step: None	Yes; 1x conversion time
● Step: low	Yes; 4x conversion time
● Step: Medium	Yes; 8x conversion time
● Step: High	Yes; 16x conversion time
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	-70 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.03 %
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.1 %; 0.3 % when SFU OFF
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.05 %; 0.2 % when SFU OFF
Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency	
● Series mode interference (peak value of interference < rated value of input range), min.	70 dB
● Common mode voltage, max.	60 V; DC
● Common mode interference, min.	90 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
● Limit value alarm	Yes; two upper and two lower limit values in each case
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	Yes; channel by channel
● Overflow/Underflow	Yes; channel by channel
Diagnostics indication LED	
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED
● for module diagnostics	Yes; green/red LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	Yes
Permissible potential difference	
between the inputs (UCM)	60 Vpp
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for applications according to AMS 2750	Yes; Declaration of Conformity, see online support entry 109757262

Subject to change without notice
© Copyright Siemens

Suitable for applications according to CQI-9	Yes; Based on AMS 2750 E
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	9.32 kg
— global warming potential, (during production) [CO2 eq]	4.97 kg
— global warming potential, (during operation) [CO2 eq]	4.79 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.449 kg
Security	
signed firmware update	Yes; firmware V2.0.0 or higher
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C; < 0 °C as of FS02
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C; < 0 °C as of FS02
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	33 g
Classifications	

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval





Miscellaneous





TUEV

General Product Approval	EMV	Test Certificates

Subject to change without notice
© Copyright Siemens

EG-Konf.	Confirmation	RCM	Type Test Certific-ates/Test Report	Special Test Certific-ate	Miscellaneous

Maritime application					other
ABS	BUREAU VERITAS	DNV	LRS	CCS (China Classifica-tion Society)	Miscellaneous

other			Dangerous goods	Environment	
Miscellaneous	Confirmation	产品合格 QC PASS	Transport Information	Environmental Con-firmations	Siemens EcoTech

Environment	
EPD	Environmental Con-firmations

last modified: 9/16/2026

Subject to change without notice
© Copyright Siemens